

Technical Specification

ProGlove LEO

WIRELESS COMMUNICATION

BLUETOOTH LOW ENERGY

BLUETOOTH RADIO	Supports Bluetooth Low Energy 4.0, 4.1, 4.2, 5.0		
FREQUENCY RANGE	Frequency band used BLE: 2400-2483.5 MHz		
MAX RADIO-FREQU. POWER TRANSMITTED	< 20dBm		
TRANSMISSION RANGE	<table border="0"> <tr> <td>3rd party device Free field: 40 m (131 ft)** Indoor: 10-20 m (33-66 ft)**</td> <td>ProGlove Gateway Free field: 70 m (230 ft)** Indoor: 30-40 m (100-130 ft)**</td> </tr> </table> <p>**may decrease in industrial environments (e.g. due to walls, metal shelving, machines)</p>	3rd party device Free field: 40 m (131 ft)** Indoor: 10-20 m (33-66 ft)**	ProGlove Gateway Free field: 70 m (230 ft)** Indoor: 30-40 m (100-130 ft)**
3rd party device Free field: 40 m (131 ft)** Indoor: 10-20 m (33-66 ft)**	ProGlove Gateway Free field: 70 m (230 ft)** Indoor: 30-40 m (100-130 ft)**		

BARCODE DECODING CAPABILITIES

1D	Auto decodes all standard 1D codes including GS1 DataBar linear codes et al.
2D	PDF417, MicroPDF417, Data matrix, QR Code, Micro QR Code, Aztec, MaxiCode et al.
POSTAL	US PostNet, US Planet, UK Postal, Australia Postal, Japan Postal, Dutch Postal (KIX) et al.

ELECTRICAL PROPERTIES

BATTERY	670 mAh, Lithium polymer (rechargeable)
CHARGING TIME	1 hours with ProGlove Charging Station
OPERATING TIME / SCANS	Approx. 4000 scans depending on the application and environmental conditions

MECHANICAL PROPERTIES

DIMENSIONS	50 x 45 x 17 mm (1.47 x 1.77 x 0.67 in)
WEIGHT	35 g (1.23 oz)

ENVIRONMENTAL CONDITIONS

DROP RESISTANCE	Resists several drops from 2 m (6.5 ft) onto concrete
TUMBLES	2000 tumbles from 0.5m
PROTECTION AGAINST DUST AND WATER	IP43
TEMPERATURE	Operating Temperature: 0°C - 50°C (32°F - 122°F) Charging Temperature: 5°C - 40°C (41°F - 104°F) Storage Temperature: -20°C - 60°C (-4°F - 140°F)
HUMIDITY	5% - 95% non condensing
ELECTROSTATIC DISCHARGE (ESD)	±8kVdc air discharge ±4kVdc contact discharge

INTERFACES

BLUETOOTH	HID Profiles
ANDROID	HID, Insight Mobile (Android) (App/SDK)
IOS	HID, Insight Mobile (iOS) (SDK)
USB	ProGlove Gateway

SCANNER PROPERTIES

READING FIELD OF VIEW	Standard range: horizontal: 45°, vertical: 33.5°
SKEW, PITCH & ROLL	Skew tolerance: ±60° Pitch tolerance: ±60° Roll tolerance: 360°
AMBIENT LIGHT	0 - 96,900 lux
AIMER	Green LED, 550 nm, 1 mW

SCAN RANGES

Minimum distance determined by symbol length, scan-angle and environmental conditions.

STANDARD RANGE

The smallest symbol in the barcode (the mil-inch (mm) number indicates the size of the smallest function in the barcode)	Possible distance between user and barcode
5 mil Code 39	2.4 in./6.1 cm to 9.5 in./24.1 cm
5 mil Code 128	2.8 in./7.1 cm to 8.7 in./22.1 cm
10 mil DataMatrix	2.9 in./7.4 cm to 8.5 in./21.6 cm
100% UPCA	1.8 in./4.6 cm to 19.5 in./49.5 cm
20 mil Code 39	2.5 in./5.1 cm to 26.0 in./66.0 cm
20 mil QR	1.2 in./3.0 cm to 14.0 in./35.6 cm

UTILITIES & ACCESSORIES*

CONFIGURATION & DEVICE MANAGEMENT	https://insight.proglove.com
DIGITAL DOCUMENTATION	https://docs.proglove.com
ANDROID INTEGRATION	Insight Mobile (Android): Provides a full featured integration for Android enterprise applications.
IOS INTEGRATION	Insight Mobile (iOS): Provides an SDK for basic integration for iOS enterprise applications.
GATEWAY INTEGRATION	ProGlove Gateway: Hardware connector to enable the full capabilities of the ProGlove Ecosystem via USB-Interface.
TRIGGER	Scanner can be triggered only with ProGlove wearables (REEL, Index-Trigger et al.)

*More Information on www.proglove.com

WARRANTY & SLA

WARRANTY	12 months factory warranty
PROGLOVE CARE	36 and 60 months maintenance contracts available. For more information please contact your ProGlove representative or visit https://proglove.com

SAFETY & REGULATORY

RADIO AND ELECTROMAGNETIC COMPATIBILITY	EU: 2014/53/EU Radio Equipment Directive (RED) FCC ID: 2A0JL-LEO IC: 23450-LEO
ELECTRICAL SAFETY	EU: acc. to 2014/53/EU Radio Equipment Directive (RED) EN 62368-1:2014 + A11:2017 INTERNATIONAL: IEC 62368-1:2014 US: UL 62368-1, 2 nd Ed, 2014-12-01 and CAN/CSA C22.2 No. 62368-1-14
LED CLASSIFICATION	Standard Range: Excluded risk group LED product according to IEC/EN 62471
ENVIRONMENTAL	RoHS Directive 2011/65/EU; Amendment 2015/863, REACH SVHC 1907/2006; WEEE

COUNTRY APPROVALS

Regulatory markings are affixed to the device, indicating that the radio modules are approved for use in the following regions: European Economic Area*, Canada, United States of America, China, Australia, New Zealand.

Detailed information on the regulatory markings can be found in the Declaration of Conformity (DoC) at www.proglove.com

*CE is valid in the European Economic Area and additional countries: Austria, Belgium, Bulgaria, Croatia, Republic of Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, United Kingdom, Iceland, Liechtenstein, Switzerland and Norway.