

OPH-1005

Barcode Laser Scanner

HIGHLIGHTS



- TFT LCD QVGA color display
- 2", 320 x 240 pixels
- (alpha)numeric keypad
- 1,5 m drop proof
- IP 54

OPH-1005

Basic product specifications

OPERATION

CPU: RX62N 32-bit MCU **O/S:** Proprietary **SOFTWARE:** Programmable in C-language. Software development kit with compiler free downloadable **RTC:** Supports year, month, day, hour, minute, second (leap year supported)

MEMORY

NAND FLASH: 128 MB **FLASHROM:** 4 MB **RAM:** 4 MB SRAM

DISPLAY

TYPE: TFT LCD QVGA color display with backlight **SIZE:** 2", 320 x 240 pixels
FONT SIZE: 6x6 / 6x12 / 8x8 / 8x16 / 8x19 / 11x19 / 12x24 dots / 16x32

OPERATING INDICATORS

VISUAL: Dual-color LED (red/green) **NON-VISUAL:** Buzzer

OPERATING KEYS

ENTRY OPTIONS: 23 keys total, 12 key (alpha)numeric keypad, 2 navigation keys, 4 function keys, 3 control keys, 1 power key, 1 scan key

COMMUNICATION

IRDA: Ver. 1.2, baudrate 1200 bps - 115.2 kbps

POWER

RECHARGEABLE BATTERY: Lithium-Ion 3.7V 1100mAh **OPERATING TIME:** Ca. 40 hours (backlight off, 1 scan / 10 sec) **DATA RETENTION TIME:** Indefinitely
CHARGING METHOD: Separate cradle CRD-1004, CRD-1006

BARCODE SCANNER OPTICS

LIGHT SOURCE: 650 nm visible laser diode **SCAN METHOD:** Vibrating mirror
SCAN RATE: 100 scans/sec **READING PITCH ANGLE:** -35 to 0°, 0 to +35°
READING SKEW ANGLE: -50 to -8°, +8 to +50° **READING TILT ANGLE:** -20° to 0°, 0 to +20° **CURVATURE:** R>15 (EAN8), R>20 (EAN13) **MIN. PCS VALUE:** 0.45
DEPTH OF FIELD: At PCS 0.9, Code 39, 70 - 450 mm / 2.76 - 17.72 in (1.0 mm / 39 mil), 50 - 320 mm / 1.97 - 12.60 in (0.5 mm / 20 mil), 50 - 200 mm / 1.97 - 7.87 in (0.25 mm / 10 mil), 55 - 120 mm / 2.17 - 4.72 in (0.15 mm / 6 mil)

SUPPORTED SYBLOGIES

BARCODE (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey **POSTAL CODE:** Chinese Post, Korean Postal Authority code **2D CODE:** Composite Codes, MicroPDF417, PDF417

DURABILITY

TEMPERATURE IN OPERATION: -10 to 50 °C / 14 to 122 °F **TEMPERATURE IN STORAGE:** -20 to 60 °C / -4 to 140 °F **HUMIDITY IN OPERATION:** 20 - 85% (non-condensing) **HUMIDITY IN STORAGE:** 20 - 85% (non-condensing)
AMBIENT LIGHT IMMUNITY: White 4,000 lx max, Fluorescent 4,000 lx max, Direct sun 80,000 lx max **DROP TEST:** 1.5 m / 5 ft drop onto concrete surface
PROTECTION RATE: IP 54

PHYSICAL

DIMENSIONS (W X H X D): 55 x 136 x 23 mm / 2.17 x 5.35 x 0.91 in **WEIGHT BODY:** Ca. 140 g / 4.9 oz (incl. Lithium-Ion battery) **CASE:** ABS, Black

REGULATORY & SAFETY

PRODUCT COMPLIANCE: CE, FCC, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

ENCLOSED ITEMS

Wrist strap

SOLD SEPARATELY

RECHARGEABLE BATTERY: Lithium-Ion 3.7V 1100mAh **CRD-1004 CRADLE:** Ethernet, communication, charging **CRD-1006 CRADLE:** Serial communication, charging

